

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

TPC 18V CORDLESS 4 SPEED HAMMER DRILL 5.0AH BLUETOOTH SET IN SYSTAINER 578286 BY FESTOOL



SKU	Option	Part	: #	Price
87434778		578286		\$1065
Model				
Туре			Hammer Drill	
SKU			87434778	
Part Number			578286	
Barcode			4014549444696	
Brand			Festool	
Packaging + Shipping				
Shipping Weight (Gross)			1.48 kg	

Pure power, controlled in four gears.

Powerful. Versatile. With four gears for every application and the best switching concept you have ever operated. Whether you are working on wood, metal or masonry, the TPC QUADRIVE is extremely durable and thanks to its brushless EC-TEC motor, has extreme resilience and endurance.

The axial impact feature is easily switched on for work with masonry. Up to 75Nm of power drives screws and drills large diameters easily, while electronic kickback stop minimises wrist injury if the tool suddenly jams.

The large number of attachments, combined with perfectly matched accessories, make the QUADRIVE an unrivalled drill for a wide range of possible uses.

Main applications

Production of wooden substructures, frame structures Installation of doors and windows Drilling and screwdriving in wood, metal and plastic Drive screws into wood up to 10x300 mm Drilling in wood up to 70 mm with Forstner drill bits Drilling with impact in brickwork or masonry

Specifications

Tool Weight (kg): 2.0 kg (with battery) Drilling Diameter Steel (mm): 13 mm No Load Speed 1st Gear (rpm): 0 - 500 min⁻¹ No Load Speed 2nd Gear (rpm): 0 - 800 min⁻¹ Drilling Diameter Wood (mm): 70 mm Battery Voltage (V): 18 V Battery Capacity (Ah): 5.2 Ah Power Source: Cordless Motor Type: Brushless Battery Type: Lithium Ion Gears: 4 Torque Adjustment 1st Gear (Nm): 2 - 20 Nm



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

Torque Adjustment 2nd Gear (Nm): 2 - 20 Nm Maximum Torque Wood (Nm): 50 Nm Maximum Torque Steel (Nm): 75 Nm Chuck Range (mm): 1.5 - 13 mm Drilling Diameter Brick (mm): 10 mm No Load Speed 4th Gear (rpm): 0 - 3600 min⁻¹ No Load Speed 3rd Gear (rpm): 0 - 2350 min⁻¹ Maximum Impact Rate (imp): 57,600 min⁻¹ Chuck Type: FastFix