

## OF 1010R 55MM PLUNGE ROUTER WITH LIGHT IN SYSTAINER 578016 BY FESTOOL



SKU	Option	Part #	Price
87434781		578016	\$1195

Model	
Type	Plunge Router
SKU	87434781
Part Number	578016
Barcode	4014549436844
Brand	Festool
Technical - Main	
Power Source	Corded
Motor Speed - No Load	9â(500 - 23â(000 minâ»Â¹
Packaging + Shipping	
Shipping Weight (Gross)	3.2 kg

### Lights on for maximum precision.

The OF 1010 R router enables you to work with maximum precision. The double-sided column clamp makes it extremely torsionally rigid and the parallel side fence can be precisely adjusted without any tools. The easily accessible working area with LED light ring provides an optimal view of the workpiece. The ring provides shadow free lighting directly on the workpiece; everything you need for extremely precise routing results. Moreover, thanks to the extensive range of accessories, the application possibilities of the OF 1010 R are virtually unlimited.

Handy: Thanks to the compact design and low weight.

Unobstructed view: Clearly visible routing area.

Well lit: Thanks to the rechargeable LED work light in the base panel.

In an instant: Quick and easy cutter changes.

Precise: Simple routing depth adjustment, accurate to 1/10 mm.

Steady: Torsionally rigid router table due to guide columns on both sides.

Parallel side fence: Quick and precise to adjust thanks to the central clamp with fine adjuster and tool free adjustable guidance jaws.

Safer: Thanks to quick-acting brake and restart protection.

Material specific: MMC electronics for optimal work and temperature monitoring.

Integrated: Chip extraction system directly integrated into the router table for D 27 and D 36 hose diameters.

### Main applications

Rounding, chamfering, rebating and profiling edges

Recessing metal fittings

Grooving rear panels, recessing dovetail batons or routing plasterboard with the guide system (edging technology)

Producing rows of holes in cabinets using the hole series system LR 32

Fashioning wooden joints with the VS 600

### Specifications

Tool Weight (kg): 3.20 kg



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

No Load Speed (rpm): 9 500 - 23 000 min<sup>-1</sup>  
Dust Extraction Connection Diameter (mm): 27/36 mm  
Collet Diameter (mm): 6 - 8 mm  
Routing Depth Adjustment Range (mm): 8.00 mm  
Power Source: Corded  
Power Consumption (W or kW): 1 010 W  
Routing stroke: 55.00 mm  
Bench opening: 50.00 mm