



Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

18V CORDLESS HEAT GUN RH18DA(H4Z) BY HIKOKI





| SKU | Option | Part # | Price |
|------|--------|-------------|-------|
| 9348 | | RH18DA(H4Z) | \$199 |

| Model | | |
|-----------------------------|---|--|
| Туре | Heat / Hot Air Gun | |
| SKU | 9348 | |
| Part Number | RH18DA(H4Z) | |
| Brand | HiKOKI | |
| Technical - Main | | |
| Air Delivery | Mode 2: 200L/min | |
| Battery Voltage (V) | 18V | |
| Dimensions | | |
| Product Weight (Net Weight) | 0.6 kg | |
| Features | | |
| Standard Inclusions | 1 x Nozzle plain, 1 x Nozzle curved surface, 1 x Nozzle round | |
| Workshop (Site) Info | | |
| Air Delivery | Mode 2: 200L/min | |
| Packaging + Shipping | | |
| Shipping Weight (Gross) | 0.648 kg | |

Features

The 18V Cordless Heat Gun has a temperature control button that can be adjusted to set the temperature in 10° C increments from 30° C to 550° C.

The easy to use two-stage switch controls the selection of low & high air volume and temperature required for various applications. Three different sized nozzles are provided for various applications. The nozzles can be removed hands free by rotating the front cover. This protects the user from burning themselves on the extremely hot nozzle after use.

The convenient integrated hook can be used to hang the tool away safely between operations

The set temperature and the battery level is displayed on the LCD panel.

Specification

Output Voltage 18V
Motor DC motor

2 Speed function High and low speed

Air temperature $\begin{array}{c} \text{Low} & 30^{\circ}\text{C to }400^{\circ}\text{C} \\ \text{High} & 30^{\circ}\text{C to }550^{\circ}\text{C} \\ \end{array}$ Time required to reach the set temperature $\begin{array}{c} 300^{\circ}\text{C to }550^{\circ}\text{C} \\ \end{array}$



Air volume

Battery

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

550°C 50 seconds Low 200L / minute High 300L / minute

Continuous operating time per charge with the Multi Volt Low Approximately 21 minutes (at 400°C)

battery BSL 36A18* High Approximately 17 minutes (at 550°C)

Compatible with HiKOKI Multi Volt and 18V slide

batteries

Dimensions L x H x W 165 x 217 x 78 mm (without battery)

Type of switch Slide switch

LCD panel

The temperature and the battery level are

displayed

Hook Positioned on the rear of the heat gun Nozzle removing mechanism Positioned on the front of the heat gun

LED light White LED

Weight 0.6 kg (without battery)

Standard accessories 1 x Nozzle plain, 1 x Nozzle curved surface, 1 x

Nozzle round