

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

125MM 1900W WALL CHASER MFE40 + 35L M CLASS VACUUM / DUST EXTRACTOR COMBO ASR 35 M ACP COMBO (AU60010070) BY METABO





9504209

Model	
Туре	Wall Chaser
SKU	9504209
Part Number	AU60010070
Barcode	9339742001312
Brand	Metabo
Size	125mm (5")
Technical - Main	
Power Source	240V 50Hz Single Phase
Motor Power (Input)	1900W
Motor Speed - No Load	5000rpm
Noise Level (Std Pressure)	93dB (A)
Sanding Disc Size	125 mm
Packaging + Shipping	
Shipping Weight (Gross)	10.48 kg

Part #

AU60010070

Option

Price

\$2299







All -purpose Vacuum Cleaner - ASR 35 M ACP: Features:

For extraction from the power tool in continuous mode, both on construction sites and in the workshop

Especially suited for extracting concrete and rock dust Compact vacuum cleaner for liquids and dry solids with commercial registration

Power socket for a power tool for using the automatical startup/shut-down of the vacuum cleaner

AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous use If the optimum suction performance falls below a certain level, the filters are vibrated immediately

High user protection: certified in accordance with EU standard for M class dusts

Automatic shut-down when vacuuming liquids once the maximum fill level is reached

Warning signal on shortfall of the minimum volume flow to

protect the user Optimum suction power by preselection of the hose diameter Automatic trailing mechanism for emptying the suction hose

completely

Antistatic basic equipment prevents static charge when using appropriate accessories

Sturdy thanks to especially large wheels and castors with wheel stop

BEYOND

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Cable winding mechanism

Practical accessory case and storage area

Specification:-

Air output max.: 4380 l/min / 157 cfm Vacuum: 270 hPa (mbar) / 3.6 psi Filter surface: 8600 cm ² / 1333 sq.inch

Input power max.: 1400 W Container volume: 35 I / 9 gal Suction hose \tilde{A}^{\sim} : 35 mm / 1 3/8 "

Hose length: 4 m / 15 ft Weight: 16 kg / 35.3 lbs Cable length: 8 m / 26 ft

Noise Emission: Sound pressure level: 69 dB(A)

Wall Chaser - MFE 40: Features:

Ideal for electric installations to lay cables and empty pipes

under plaster with cutting depths up to 40 mm

Maximum work progress by means of powerful motor, constant speed and two-speed high-performance gear

Robust aluminium die-cast hood with rubber rolls and optimal

handle position for comfortable guiding of the machine

Pushing cut for optimal view of the marking line Channel width and cutting depth can be set

Metabo Marathon motor with patented dust protection for

long service life

Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load

Electronic soft start and restart protection for safe working

LED signal informs about overload or active restart protection

Clean, low-dust working by means of connecting a Metabo all-purpose vacuum cleaner (certified with ASR 35 M ACP) Suitable for slitting grooves up to a width of 30 mm without

centre in one workstep (with special accessories)

Also suitable for cutting with only one diamond cutting disc Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the disc stop unexpectedly

Specification:-

Adjustable cutting depth: 10 - 40 mm // 3/8 - 1 9/16 " Possible groove widths: 9 / 15.5 / 22 / 28.5 / 35 mm / 3/8 / 5/8

/ 7/8 / 1 1/8 / 1 3/8 "

Cutting disc Ã": 125 mm / 5 " Rated input power: 1900 W Output power: 1120 W No-load speed: 5000 rpm

Revolutions at rated load: 4200 rpm

Torque: 6 Nm / 53 in-lbs

Weight (without power cable): 4.6 kg / 10.1 lbs

Cable length: 4 m / 13 ft

Noise emission: Sound pressure level: 93 dB(A)

Sound power level (LwA): 104 dB(A) Uncertainty of measurement K: 3 dB(A)

The machine shown may differ in equipment and technical details depending on the configuration. Kindly pay attention to delivery scope and product description. Accessories

included only if listed in the delivery scope.