

UNC HSS TAP SET BY BORDO



SKU	Option	Part #	Price
9803129	Size: 1/2" x 13TPI	3032-1/2TS	\$83.2
9803125	Size: 1/4" x 20TPI	3032-1/4TS	\$46.5
9803127	Size: 3/8" x 16TPI	3032-3/8TS	\$56.2
9803126	Size: 5/16" x 18TPI	3032-5/16TS	\$50.9
8001784	Size: 5/8" x 13TPI	3032-5/8TS	\$149
9803128	Size: 7/16" x 14TPI	3032-7/16TS	\$73.84

Model	
Type	Tap Set
SKU	9803129
Part Number	3032-1/2TS
Barcode	9326518027416
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

HSS UNC Hand and Machine Tap Set.

Unified National Coarse thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNC is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

This thread series is commonly used in the mass production of bolts, screws and nuts.

It is used for threading into lower tensile strength materials (bronze, brass, aluminium and plastics) to obtain the best resistance to stripping of the internal thread.

It is also used on quick assembly or disassembly or if corrosion or slight damage is possible.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Manufactured from HSS this general purpose tap is designed for use in medium tensile materials and is for hand or general machine use.

Options

3032-1/2TS



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

3032-1/4TS
3032-3/8TS
3032-5/16TS
3032-5/8TS
3032-7/16TS