



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

TITEBOND II PREMIUM EXTEND - TBIIEXTEND473 BY TITEBOND



SKU	Option	Part #	Price
9803352		TBIIEXTEND473	\$22.9

Model	
Type	Adhesive / Sealant
SKU	9803352
Part Number	TBIIEXTEND473
Barcode	037083041347
Brand	Titebond
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Description

Titebond II Premium Extend is a slower-setting version of the Titebond Premium range.

This glue combines weatherproof performance (ANSI Type II water-resistance) with a slower set and is ideal for exterior applications that involve more complex assemblies. It provides a translucent glue line, offers excellent sandability and is unaffected by finishes. Titebond II Extend offers superior performance on all common wood species, particleboard, MDF, plywood and other porous materials. In addition, it is compatible for use with Hot Press and radio frequency (R-F) gluing systems.

Features

Passes Type II Water-resistance testing

Slower setting time – longer open time

Hot press and R-F compatible

Solvent-resistant

Excellent sandability

Application Temperature: Above 15°C

Open Assembly Time: 15 minutes (21°C./50% RH)

Total Assembly Time: 20-25 minutes (21°C./50%RH)

Minimum Required Spread : Approximately 6ml or 250 square feet per gallon

Required Clamping Pressure: Enough to bring joints tightly together (generally, 30-80 psi for HPL, 100-150 psi for softwoods, 125-175 psi for medium woods and 175-250 psi for hardwoods)

Method of Application: Easily spread with a roller spreader or brush, or may be transferred to plastic bottles for finer gluing applications.

Cleanup: Damp cloth while glue is wet. Scrape off and sand dried excess.

More information here.