

#### 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

# 900W BEVELLING TOOL KFM 9-3 RF (601751750) BY METABO





| SKU     | Option | Part #    | Price  |
|---------|--------|-----------|--------|
| 9803539 |        | 601751790 | \$1799 |

| Model                       |                 |  |
|-----------------------------|-----------------|--|
| Туре                        | Bevelling Tool  |  |
| SKU                         | 9803539         |  |
| Part Number                 | 601751790       |  |
| Barcode                     | 4007430293435   |  |
| Brand                       | Metabo          |  |
| Technical - Main            |                 |  |
| Motor Speed - No Load       | 4500 - 11500RPM |  |
| Dimensions                  |                 |  |
| Product Weight (Net Weight) | 2.5 kg          |  |
| Features                    |                 |  |
| Standard Inclusions         | MetaLoc case    |  |
| Packaging + Shipping        |                 |  |
| Shipping Weight (Gross)     | 1.48 kg         |  |







#### Features:-

Compact metal bevelling tool for 45  $^{\circ}$  chamfers and radii of 2 to 3 mm at visible edges

Surfaces free from oxide and burrs as ideal preparation for the application of powder or paint coatings for maximum protection from corrosion

One-touch controller: Patented, tool-free setting of the cutting depth in 0.1 steps; stop points for short setting times, and protection against unintentional adjustment of the cutting depth when working

Slim cutter head with standard carbide indexable inserts and ball-bearing stationary seal ring for working in tubes and in

Guide stop for a uniform finish and high quality of the surface when processing straight sheets

Metabo Long-life motor with patented dust protection for long service life

Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load

Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly

Electronic overload protection, soft start and restart protection

Slim design for ideal handling

### **Specifications:-**

Type of edges: Chamfer and radius



## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Max. chamfer width 45 °: 6mm / 1/4 " Max. chamfer height at 45 °: 4mm / 5/32 "

Possible radii: R2 / R3

Grading of cutting depth setting: 0.1 mm / 0.004 " mm

Curves smallest internal  $\tilde{A}^{\tilde{\ }}\colon 13m$