



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## MC CHROME TAP SET 10 X 1.5MM - 4220-10.00TS BY BORDO



SKU	Option	Part #	Price
9804132		4220-10.00TS	\$36

Model	
Type	Tap Set
SKU	9804132
Part Number	4220-10.00TS
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



### About this item:

10 x 1.5mm MC Chrome Tap Set

Chrome Alloy Metric Coarse Hand Tap Set.

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Metric Coarse angle of thread is 60 degrees.

The crest is flat and the thread has clearance at the root allowing external thread and internal thread to engage well.

Larger root radius and lower thread height enable easy screw thread processing and increase thread screw strength.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in millimetres).

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.