

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

UNF CHROME TAP SET BY BORDO





SKU	Option	Part #	Price
9804136	Size: 1/2" x 20TPI	4234-1/2TS	\$44
9804134	Size: 1/4" x 28TPI	4234-1/4TS	\$28
9804135	Size: 5/16" x 24TPI	4234-5/16TS	\$31

Model	
Туре	Tap Set
SKU	9804136
Part Number	4234-1/2TS
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

About this product:

Chrome Alloy UNF Hand Tap Set.

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in nonferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

The thread profile of UNF is the same as for metric threads and is described in the JIS B0206 standard.

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

The thread is described by its major diameter and the number of threads per inch of length (TPI). When used on external threads this series has greater tensile stress area than coarse threads of the same size. Fine series threads will resist stripping out better than coarse threads in areas where the external and mating internal threads are subjected to loads equal to or greater than the capacity of the screw or bolt.

Fine threads are also used where the length of engagement is limited 1-1/4 or where wall thickness demands a fine pitch. Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.

Options

4234-1/2TS 4234-1/4TS 4234-5/16TS