



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

MF BOTTOMING HSS TAP BY BORDO



SKU	Option	Part #	Price
8709075	Size: 10mm x 1.25mm	3021-10.00B	\$46
8709079	Size: 12mm x 1.5mm	3021-12.00B	\$53
8709082	Size: 14mm x 1.5mm	3021-14.00B	\$77.9
8709097	Size: 25mm x 1.5mm	3023-25.00B	\$107.95
9804252	Size: 7mm x 0.75mm	3021-7.00B	\$29.95
8709086	Size: 8mm x 1mm	3021-8.00B	\$31.95

Model	
Type	Bottoming Tap
SKU	9804252
Part Number	3021-7.00B
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



About this product:

HSS Metric Fine Bottoming Hand and Machine Tap.

Metric Fine angle of thread is 60 degrees.

The crest is flat and the thread has clearance at the root allowing external thread and internal thread to engage well.

Larger root radius and lower thread height enable easy screw thread processing and increase thread screw strength.

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in millimetres).



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.

Manufactured from HSS this general purpose tap is designed for use in medium tensile materials and is for hand or general machine use.